

CERTIFICATE OF COMPLIANCE

Certificate Number 20140807-E146589
Report Reference E146589-19970529
Issue Date 2014-AUGUST-07

Issued to: BARKSDALE INC
3211 FRUITLAND AVE
LOS ANGELES CA 90058

**This is to certify that
representative samples of**

TELEMETERING EQUIPMENT FOR USE IN HAZARDOUS
LOCATIONS

Refer next page for Models/Product

Have been investigated by UL in accordance with the
Standard(s) indicated on this Certificate.

Standard(s) for Safety:

UL 1203, Explosion-Proof and Dust-Ignition-Proof Electrical
Equipment for Use in Hazardous (Classified) Locations
CAN/CSA C22.2 No. 30-M1986, Explosion-Proof
Enclosures for Use in Class I Hazardous Locations,
Reaffirmed 1988 and ANSI/ISA 12.27.01, Requirements for
Process Sealing Between Electrical Systems and
Flammable or Combustible Process Fluids

Additional Information:

See the UL Online Certifications Directory at
www.ul.com/database for additional information

Only those products bearing the UL Listing Mark for the US and Canada should be considered as
being covered by UL's Listing and Follow-Up Service meeting the appropriate requirements for US
and Canada.

The UL Listing Mark for the US and Canada generally includes: the UL in a circle symbol with "C" and

"US" identifiers:  the word "LISTED"; a control number (may be alphanumeric) assigned by UL;
and the product category name (product identifier) as indicated in the appropriate UL Directory.

Look for the UL Listing Mark on the product.



William R. Carney, Director, North American Certification Programs
UL LLC

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please
contact a local UL Customer Service Representative at www.ul.com/contactus



CERTIFICATE OF COMPLIANCE

Certificate Number 20140807-E146589
Report Reference E146589-19970529
Issue Date 2014-AUGUST-07

This is to certify that representative samples of the product as specified on this certificate were tested according to the current UL requirements.

USL/CNL - Pressure Transducer, Models 423X, 425X and 426X, followed by -01, -03, -04, -05, -06, -07, -08, -10, -12, -13, -14, -15, -16, -17, -18, -19, -21, -22, -23 or -25 may be followed by -A suffix, may be followed by replace with -P1, -P3, -P4, P5, -P6, -P7, -P10, -P11, or -P12 with suffix, may be followed by -Z, -W, Q1-Q999 or - S suffix (may be followed by additional digits), for use in Class I, Groups A, B, C and D; Class II, Groups E, F and G Hazardous Locations.



William R. Carney, Director, North American Certification Programs
UL LLC

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact a local UL Customer Service Representative at www.ul.com/contactus

