

CERTIFICATE OF COMPLIANCE

Certificate Number 20160302-E302981
Report Reference E302981-20060213
Issue Date 2016-MARCH-02

Issued to: BARKSDALE INC
3211 FRUITLAND AVE
LOS ANGELES CA 90058

This is to certify that POWER CIRCUIT AND MOTOR-MOUNTED APPARATUS
representative samples of See addendum page

Have been investigated by UL in accordance with the
Standard(s) indicated on this Certificate.

Standard(s) for Safety: Standard for Industrial Control equipment, UL508
Industrial Control Equipment, CSA C22.2 No. 14-13

Additional Information: See the UL Online Certifications Directory at
www.ul.com/database for additional information

Only those products bearing the UL Certification Mark should be considered as being covered by UL's
Certification and Follow-Up Service.

Look for the UL Certification Mark on the product.



Bruce Mahrenholz, Director North American Certification Program
UL LLC

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please
contact a local UL Customer Service Representative at <http://ul.com/aboutul/locations/>



CERTIFICATE OF COMPLIANCE

Certificate Number 20160302-E302981
Report Reference E302981-20060213
Issue Date 2016-MARCH-02

This is to certify that representative samples of the product as specified on this certificate were tested according to the current UL requirements.


USL, CNL: Pressure Transducer, Model 423, followed by H3, H3-E, H5, H5-E, H6, H6-E, T4, T4-E, T5, T5-E, T8, or T8-E, followed by -01, -21, -03, -22, -04, -05, -06, -07, -09, -19, -10, -12, -13, -14, -15, -16, -17, or -18, may be followed by -Z10, -Z11, -Z12, -Z15, -WXX, or - 4 digits, may be followed by P1 - P10, or Q1-Q99, or -S, and -U.

Pressure Transducer, Model 425, followed by H3, H3-E, H5, H5-E, H6, H6-E, T4, T4-E, T5, T5-E, T8, or T8-E, followed by -23, -25, -01, -21, -22, -03, -04, -05, -06, -07, -08, -19, -10, -11, -12, -13, -14, -15, -16, -17, and -18, may be followed by -Z10, -Z11, -Z12, -Z15, -WXX, or - 4 digits, may be followed by P1 - P10, or Q1-Q99, or -S, and -U.

Pressure Transducer, Model 426, followed by H3, H3-E, H5, H5-E, H6, H6-E, T4, T4-E, T5, T5-E, T8, or T8-E, followed by -23, -25, -01, -21, -03, -22, -04, -05, -06, -07, -08, -19, -10, -11, -12, -13, -14, -15, -16, -17, and -18, may be followed by -Z10, -Z11, -Z12, -Z15, -WXX, or - 4 digits, may be followed by P1 - P10, or Q1-Q99, or -S, and -U.

Pressure Transducer, Model 420, followed by H3, H3-E, H5, H5-E, H6, H6-E, T4, T4-E, T5, T5-E, T8, or T8-E, followed by -01, -03, -04, -05, -06, -07, -08, -10, -11, -12, -13, -14, -15, -17, and -18, may be followed by -Z10, -Z11, -Z12, -Z15, -WXX, or - 4 digits, may be followed by P1 - P10, or Q1-Q99, or -S, and -U.

Pressure Transducer, Model 422, followed by H3, H3-E, H5, H5-E, H6, H6-E, T4, T4-E, T5, T5-E, T8, or T8-E, followed by -25, -21, -22, -01, -03, -04, -05, -06, -07, -08, -10, -11, -12, -13, -14, -15, -17, and -18, may be followed by -Z10, -Z11, -Z12, -Z15, -WXX, or - 4 digits, may be followed by P1 - P10, or Q1-Q99, or -S, and -U.



Bruce Mahrenholz, Director North American Certification Program
UL LLC

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact a local UL Customer Service Representative at <http://ul.com/aboutul/locations/>

